

# 2008 Grand Touring Appendix A.3.



	Manufacturer and Model	Engine Displacement	Base Weight	Front Tire Size	Front Wheel (max.)	Rear Tire Size	Rear Wheel (max.)	Restrictor or Boost Limit	Engine Speed Limit	Front Axle Weight
		(Maximum, cc)	(with driver, lbs)	(Toyo R888)		(Toyo R888)			(rpm)	(min. with driver, lbs)
<b>Full Eligibility</b>	*Aston Martin DB9 (2006-)	5935	3200	275/35	11x18	335/30	13x18	60.8mm (20%)	7000	1600
	BMW E46 M3 (99-05)	3246	2900	245/40	9.5x18	275/35	11x18	n/a	8200	1450
	Cadillac CTS-V (2004-)	6026	3200	275/35	11x18	335/30	13x18	69.7mm (40%)	7400	1600
	Chevrolet Corvette C5 (97-04)	5780	3025	275/35	11x18	335/30	13x18	n/a	7400	1513
	Chevrolet Corvette C6 (2005-)	6026	3150	275/35	11x18	335/30	13x18	**66.7mm (45%)	7400	1575
	Dodge Viper (Competition Coupe) (2003-)	8284	3200	305/35	11x18	335/30	13x18	n/a	6200	1600
	*Ford Mustang Cobra (2005-)	5951	3150	275/35	11x18	335/30	13x18	n/a	8000	1575
	Pontiac GTO (2004-)	6026	3050	275/35	11x18	335/30	13x18	80.5mm (20%)	7400	1525
	Porsche 996 GT-3 (98-05)	3600	2870	245/40	9.5x18	305/35	12x18	68.6mm (30%)	8900	1665 †
	Porsche 997 GT-3 (2006)	3795	2970	265/35	10.5x18	305/35	12x18	TBD	8900	1723 †
	Porsche 996 (AWD) (tt) (98-05)	3600	3050	305/35	11x18	335/30	13x18	1300mb	7000	1769 †
	*Subaru STi (AWD)(T)(2005-)	2507	3050	305/35	11x18	305/35	11x18	1800mb	8000	1733

<b>Partial Eligibility</b>	<b>(Cars classified, but homologation incomplete)</b>									
	Manufacturer and Model	Engine Displacement	Base Weight	Front Tire Size	Front Wheel (max.)	Rear Tire Size	Rear Wheel (max.)	Restrictor or Boost Limit	Engine Speed Limit	Front Axle Weight
		(Maximum, cc)	(with driver, lbs)	(Toyo R888)		(Toyo R888)			(rpm)	(min. with driver, lbs)
	Audi S-4 (00-02)	2796	2900	275/35	10x18	275/35	10x18	1300mb	7400	1595
	Dodge Viper GTS (-2002)	8037	3200	305/35	11x18	335/30	13x18	57.2mm (20%)	6300	1600
	GM F-body (99-03)	5824	3000	275/35	11x18	335/30	12x18	n/a	8000	1500

**(Cars classified, but homologation incomplete)**

Audi RS-6 (03-04)	4172	TBD	305/35	11x18	305/35	11x18	TBD	6500	TBD
Ferrari 430 (2006-)	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Lamborghini Gallardo Superleggera (2007-)	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Lexus IS-F (2007-)	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Lotus Exige (2007-)	TBD	TBD	245/40	10x18	275/35	10x18	TBD	TBD	TBD
Mitsubishi Lancer Evo 9 (2007-)	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Volvo S60/R	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD

\* Denotes cars with VTS in draft form that are approved to race. Changes may be made on an accelerated basis until the VTS is finalized. When the VTS is finalized, the asterisk will be removed from Appendix A.

\*\* The Corvette C6 has 5% more restrictor assigned for using an alternate sequential gearbox due to reliability issues. Any Corvette C6 using the Tremec H-Pattern gearbox may use a 40% (69.7mm) restrictor.

† Minimum rear axle weight.