
90APPENDIX A.1: NOTES

A.1.1: Under **Manufacturer and Model**, a 1 indicates a vehicle with VTS in Draft form. Changes may be made on an accelerated basis.

APPENDIX A.2: GRAND TOURING (GT)

A.2.1: FULL ELIGIBILITY

Vehicles listed are eligible to compete in World Challenge GT.

Manufacturer and Model	Engine Displacement (Maximum, CC)	Base Weight (with driver, lbs)	Restrictor and/or Manifold Pressure Limit	Ride Height (Minimum, in)	Front Tire Size (Pirelli P Zero)	Front Wheel (Maximum)	Rear Tire Size (Pirelli P Zero)	Rear Wheel Size (Maximum)	Engine Speed Limit (rpm)
Aston Martin DB9 (06-)	5935	3200	60.8mm (20%)	3.00	275/645	11x18	305/675	13x18	7000
Chevrolet Corvette C6 (05-)	6026	3050	69.7mm (40%) ⁴	3.00	275/645	11x18	305/675	13x18	7400
	6162	2950	-	3.00	275/645	11x18	305/675	13x18	6500
Dodge Viper Comp Coupe (03-07)	8284	3200	58.5 mm (20%)	3.00	305/645	11x18	305/675	13x18	6200
Ford Mustang (2005-)	5951	3200 ⁵	75.3 mm (30%)	3.00	305/645	11x18	305/675	13x18	7400
Lamborghini Gallardo (03-08) ¹	4961	3150	-	3.00	275/645	11x18	305/675	13x18	8000
Lotus Exige S (07-) ¹	1840	2400	2500 mbar	3.00	245/645	10X18	245/645	10X18	TBD
Mercedes-Benz SLR McLaren	5439	3350	62.9mm (35%)	3.00	305/645	11x18	305/675	12x18	7000
Nissan GT-R (09-) ¹	3800	3500	2200 mbar	3.00	305/675	12x18	305/675	12x18	7000
Porsche 997 GT3 (06-09)	3795	2870 ⁽⁶⁾	-	3.00	275/645	10.5x18	305/675	12x18	8900
Porsche 997 GT3 (10-) ¹	3797	2820	-	3.00 ⁵	275/645	10.5x18	305/675	12x18	8500
Volvo S60 (04-09) ¹	2577	3350	2750 mbar	3.00	305/675	12x18	305/675	12x18	7800

4: Corvette C6 using the Tremec H-Pattern gearbox may use a 30% (75.3 mm) restrictor.

5: Minimum Ride Height forward of the front axle is 2.75 inches.

6: Can have a carbon roof with a 20 lbs. weight penalty.

A.2.2: PARTIAL ELIGIBILITY

Vehicles listed have been out of production worldwide more than four years, and may not compete in more than five World Challenge GT races per year unless authorized by SCCA Pro Racing, per Article 2.6.6.

Manufacturer and Model	Engine Displacement (Maximum, CC)	Base Weight (with driver, lbs)	Restrictor and/or Manifold Pressure Limit	Ride Height (Minimum, in)	Front Tire Size (Pirelli P Zero)	Front Wheel (Maximum)	Rear Tire Size (Pirelli P Zero)	Rear Wheel Size (Maximum)	Engine Speed Limit (rpm)
BMW E46 M3 (99-06)	3246	2900	-	3.00	245/645	9.5x18	275/645	11x18	8200
Pontiac GTO (04-06)	6026	3000	-	3.00	275/645	11x18	305/675	13x18	7400
Porsche 996 GT3 (98-05)	3600	2850	73.3mm (20%)	3.00	275/645	9.5x18	305/675	12x18	8900
Porsche 996 (AWD TT) (00-05)	3600	3050	2300 mbar	3.00	275/645	11x18	305/675	13x18	7000

A.2.3: CLASSIFIED

Vehicles listed have been classified into World Challenge GT, but are not eligible to compete until homologation has progressed.

Manufacturer and Model	Engine Displacement (Maximum, CC)	Base Weight (with driver, lbs)	Restrictor and/or Manifold Pressure Limit	Ride Height (Minimum, in)	Front Tire Size (Pirelli P Zero)	Front Wheel (Maximum)	Rear Tire Size (Pirelli P Zero)	Rear Wheel Size (Maximum)	Engine Speed Limit (rpm)
Ferrari F430	TBD								
Ford GT	TBD								
Lexus IS (07)	4711	TBD	TBD	3.00	275/645	11x18	305/645	13x18	TBD

APPENDIX A.3: GRAND TOURING SPORT (GTS)

A.3.1: FULL ELIGIBILITY

Vehicles listed are eligible to compete in World Challenge GTS.

Manufacturer and Model	Engine Displacement (Maximum, CC)	Base Weight (with driver, lbs)	Restrictor and/or Manifold Pressure Limit	Ride Height (Minimum, in)	Front Tire Size (Pirelli P Zero)	Front Wheel (Maximum)	Rear Tire Size (Pirelli P Zero)	Rear Wheel Size (Maximum)	Engine Speed Limit (rpm)
jk	2408	2750	-	3.50 ⁷	245/620	8x17	245/620	8x17	7800
Acura TSX (04-08)	2408	2850	-	3.50 ⁷	245/620	8x17	245/620	8x17	7800
Acura TSX (04-08) Limited Prep.	2408	2725	-	3.50 ⁷	245/620	8x17	245/620	8x17	7800
Acura TSX (09-)	2408	2750	-	3.50 ⁷	245/620	8x17	245/620	8x17	7800
BMW E46 325 (99-05)	2554	2750	-	3.50 ⁷	245/620	8x17	245/620	8x17	8100
BMW E46 M3 (01-06)	3246	3100	-	3.50 ⁷	275/645	10x18	275/645	10x18	8300
BMW E90 325 (06-)	2559	2850 ⁴	-	3.50 ⁷	245/620	8x17	245/620	8x17	8300
Chevy Camero 2010	6162	3400	TBD	3.50	305/645	10x18	305/645	10x18	6600
Ford Mustang FR500S (08) ¹	4600	3300	-	3.00	305/645	10x18	305/645	10x18	7200
Ford Mustang Boss 302 S	5000	3400	TBD	3.5	305/645	10x18	305/645	10x18	TBD
Honda Civic (96-00)	-	2350	-	3.50	225/620	17	225/620	17	-
Honda S2000	2200	2400	-	3.50	245/620	8x17	245/620	9.5/17	8,000
Lotus Exige S (07) ¹	1840	2100	1600 mbar	3.50	225/620	7x17	245/620	8.5x17	8500
Mazda 3 (10-) ¹	2489	2650	-	3.50 ⁷	245/620	8x17	245/620	8x17	8000
Mazda 6 (03-08)	2276	2850 ⁵	-	3.50 ⁷	245/620	8x17	245/620	8x17	8300
Pontiac Solstice GXP (07-09) ¹	2000	2950	2375 mbar	3.50	275/645	9.5x18	275/645	9.5x18	6300
Porsche Cayman S (06-) ¹	3387	2900	-	3.50	245/645	9x18	305/645	11x18	7300
Porsche 996 GT3 (03-04)	3800	3150	-	3.50	245/645	9x18	305/645	11x18	7300
Porsche 996 911	3600	2900	-	3.50	245/645	9x18-	305/645	11x18-	6800

⁴ BMW E90 325 using a dry sump must add 10 lbs.

⁵ Mazda 6 using a dry sump must add 10 lbs.

⁶ Acura TSX (04-08) using the OE transmission may race with no restrictor

⁷ Ride height is 3.00 inches ahead of the front axle.



A.3.2: CLASSIFIED

Vehicles listed have been classified into World Challenge GTS, but are not eligible to compete until homologation has progressed.

Year	Manufacturer and Model	Year	Manufacturer and Model
2008-	BMW M3 E92		
2006-2009	BMW Z4 Coupe 3.2	2009	Hyundai Genesis
2002-2008	BMW Z4 Coupe 3.0	2010-	Nissan 370Z
2002	BMW M Coupe	2003-2009	Subaru WRX STI
1999-2002	BMW Z4 M Coupe		
2005-2009	BMW 335i		
2010-	Chevrolet Camaro		
2008-2009	Dodge Challenger		

APPENDIX A.4: TOURING CAR (TC)

A.4.1: FULL ELIGIBILITY

Vehicles listed are eligible to compete in World Challenge TC.

Manufacturer and Model	Engine Displacement (Maximum, CC)	Base Weight (with driver, lbs)	Restrictor and/or Manifold Pressure Limit	Ride Height (Minimum, in)	Front Tire Size (Pirelli P Zero)	Front Wheel (Maximum)	Rear Tire Size (Pirelli P Zero)	Rear Wheel Size (Maximum)	Engine Speed Limit (rpm)
Acura TSX (04-08) ¹	2354	2800	-	3.50	245/620	8x17	245/620	8x17	7800
Audi TT (01-06) ¹	1781	2800	TBD	3.50	245/620	8x17	245/620	8x17	6800
Chevrolet Cobalt SS (06) ¹	2001	2800	-	3.50	245/620	8x17	245/620	8x17	7500
Chevrolet Cobalt SS (08) ¹	1998	3000	1900 mbar	3.50	245/620	8x17	245/620	8x17	6700
Honda Civic Si (06-) ¹	1998	2750 ⁴	-	3.50	245/620	8x17	245/620	8x17	8600
Honda Civic Si (01-05) ¹	2045	2800	-	3.50	245/620	8x17	245/620	8x17	7800
Honda Civic Si 2.4L (01-05) ¹	2409	2800	-	3.50	245/620	8x17	245/620	8x17	7800
Lexus IS300 (01-05) ¹	3067	2900	-	3.50	245/620	8x17	245/620	8x17	7300
Mazda MAZDASPEED3 ¹	2300	3025	40 mm, 1900 mbar	3.50	245/620	8x17	245/620	8x17	7000
Mazda RX-8 (04-08) ¹	1308	2800	-	3.50	245/620	8x17	245/620	8x17	9000
Mini Cooper S (01-06) ¹	1598	2300	TBD	3.50	225/620	7x17	225/620	7x17	TBD
Nissan Altima (08-) ¹	3498	TBD	-	3.50	245/620	8x17	245/620	8x17	6600
Scion tC (05-08) ¹	2362	2800	1820 mbar	3.50	245/620	8x17	245/620	8x17	7000
Volkswagen GTI T3 (06-08) ¹	1984	3000	-	3.50	245/620	8x17	245/620	8x17	TBD
Volkswagen Jetta GLI / Golf GTI (05-10) ¹	1984	2975	1800 mbar	4.00	245/620	8x17	245/620	8x17	6800
Volvo C30 (2011-)	2500	TBD	TBD	3.5	245/620	8/17	245/620	8/17	6500

⁴ Honda Civic Si (06-) using the stock USDM Si engine may reduce base weight by 150 lbs. See VTS Sheet for further information.

A.4.2: CLASSIFIED

2011 Appendix A



Vehicles listed have been classified into World Challenge TC, but are not eligible to compete until homologation has progressed.

Year	Manufacturer and Model
2003-2005	Audi TT 1.8 L turbo
	BMW 328i
2006	BMW 330i Sedan
2001-2003	BMW 330i/Ci
2004	BMW E46 330
2008-2009	Chevrolet Cobalt SS
2006	Honda Civic SI 2.0

Year	Manufacturer and Model
2008	Honda Civic Si 2DR and 4DR
2006	Hyundai Tiburon (2.7)
2007	Subaru Legacy Spec B Sedan 2007 2.5